

PS4 Paging Sequence

Canada
4110 - 79th Street N.W.
Calgary, Alberta
Canada T3B 5C2
Tel: 403 288 2706
Toll Free 800 661 9406
Fax: 403 288 5935
info@interalia.com

United States
10340 Viking Drive,
Suite 135
Eden Prairie, Minnesota
U.S.A. 55344
Tel: 952 942 6088
Toll Free 800 531 0115
Fax: 952 942 6172
info@interalia.com

United Kingdom
Bridge End Road
Grantham, Lincolnshire
England NG31 7TS
Tel: +44 (0) 1476 594207
Fax: +44 (0) 1476 594208
info@interalia.com

TECHNICAL SPECIFICATIONS

RECORDING TIME

- 3 Minute base unit
- Additional memory is available in 1 minute increments up to a maximum of 17 minutes

NUMBER OF LINES

- 5 Input Station channels
- 1 Page Output channel

NUMBER OF ANNOUNCEMENTS

- 30 individual announcements

BATTERY BACKUP

- Announcer operates for up to 2 hours, from a fully charged battery, during a power interruption
- 48 hour battery recharge

CONTROL CONTACT

- 0.3 A / 60 VDC
- 1.0 A / 24 VDC
- 0.5 A / 120 VAC

VOICE ENCODING/DECODING

- 8 KHz sampling rate, 8 bits/sample (PCM)

FREQUENCY RESPONSE

- 200 Hz to 3.4 KHz (+3 dB)

PAGE OUTPUT LEVEL

- Adjustable to a maximum of -9 dBm

POWER SUPPLY

- 110/120 VAC, 60 Hz, 0.2 A, 15W

FUSE RATINGS

- AC Power: MDL 0.25A Slow Blow
- Battery: MDL 2.0A Slow Blow

DIMENSIONS

- 1.75in.(4.5cm) H x 16.25in.(41cm) W x 9.25in.(23.5cm) D

WEIGHT

- 13 lbs (6 Kg)

APPROVALS

- FCC, DOC, CSA/NTRL

**Specifications are approximate and are subject to change without notice.



For more information visit: www.interalia.com

Interalia Delivering Messages: Simply, Clearly, Reliably

